



C4630 SE IR Remote Control Instruction Manual

Box Contents

Your C4630 SE IR Remote Control box should contain the following items: (1) x C4630 SE IR Remote Control; (2) x AA batteries.

Range

The C4630 SE IR Remote Control has a range of approximately 15 – 30 feet from the IR receiver.

C4630 SE Remote Control Buttons (see Figure 1)

NOTE: The C4630 SE does not have a built-in IR receiver. To use this remote control an optional Sonance OptiLinQ® IR receiver must be installed in at least one C4630 SE Main Keypad IR Receiver Holster. See the C4630 SE or C4630 SE Keypad Instruction Manuals for details.

The buttons on the C4630 SE Remote Control will perform the same functions as the correspondingly-named buttons on the C4630 SE Main and Numeric Keypads. Additionally, the remote also has an ALL OFF button and an OK button.

Like the C4630 SE Keypad buttons, each remote control button has three different actions: PRESS, PRESS-AND-HOLD and DOUBLE-PRESS. This allows the remote to duplicate the functions of the C4630 SE Keypads.

The following button functions are available “out-of-the-box” on the C4630 SE Remote Control:

ZONE VOLUME UP/DOWN buttons: PRESS = Volume UP/Down in the local zone.

MUTE button: PRESS = Mute/un-Mute the local zone; PRESS-AND-HOLD = Mute/un-Mute all zones designated for PARTY MODE.

Zone SOURCE SELECTOR buttons: PRESS = Select that source in the local zone; PRESS-AND-HOLD = Select that source in all zones designated for PARTY MODE. Pressing a Source Select button in a zone that is OFF will turn that zone ON.

Zone OFF button: Turns the local zone OFF


All OFF Button: Turns-OFF all zones in the system, including any zones being run by multiple C4630 SEs that are connected via their SYNC connections (see page 16 of the *C4630 SE Instruction Manual* for details).

OK Button: Provides a discrete confirmation command for use with devices requiring that an additional “select” or “enter” command following a numeric button entry.

The **Numeric buttons** and the **Zone Source Control buttons** will not function unless the C4630 SE has been programmed by the Sonance Control Manager.

Additional PRESS, PRESS-AND-HOLD, DOUBLE-PRESS, source component control and macro trigger functions require programming with the Sonance Control Manager software. The Sonance Control Manager can also be used to change any of the above out-of-the-box button functions.

Note: The remote's keypad is covered with a removable film to protect it during manufacture and shipping.



SONANCE • 212 Avenida Fabricante • San Clemente, CA 92672-7531

800-582-7777 or 949-492-7777 • FAX: 949-361.5151

Technical Support: 800-582-0772

www.sonance.com



Technical Assistance and Service

If you have any questions about the operation or installation of this product, please call our Technical Assistance Department on any business day at (800) 582-0772 or (949) 492-7777; from 7 a.m. to 5 p.m., PST.

If this product should need repair or service, contact your Sonance Authorized Dealer for help, or use the following procedure:

1. Prior to calling, note the product's model number, serial number, purchase date, and the name and address of the dealer where you purchased the product.
2. Contact our Technical Assistance Department at the above number(s) and describe the problem the unit is experiencing. If applicable, they will issue a Return Authorization Number.
3. If you're directed to return the unit to Sonance for repair, pack the unit in its original shipping carton. If needed, you can obtain replacement packaging from us for a small charge. Note: it is best if you place the box into an additional outer "overcarton" before shipment to minimize a chance of theft in shipment. Please include a copy of the original bill of sale inside the package.
4. Contact a package delivery service such as United Parcel Service or Federal Express to arrange prepaid (not collect) shipping. Do not use the U.S. Postal Service.

IMPORTANT: Freight collect shipments will be refused.

5. Write the Return Authorization Number on the outside of the shipping carton.

6. Ship the packaged unit to:

Quality Assurance Department
Sonance
212 Avenida Fabricante
San Clemente, CA 92672-7531

Limited Warranty Coverage (U.S.A. Only)

Sonance warrants to the original retail purchaser only that this Sonance product will be free from defects in materials and workmanship for a period of five (5) years, provided the product was purchased from a Sonance Authorized Dealer.

Defective products must be shipped, together with proof of purchase, prepaid insured to the Authorized Sonance Dealer from whom they were purchased, or to the Sonance factory at the address listed on this instruction manual. Freight collect shipments will be refused. It is preferable to ship this product in the original shipping container to lessen the chance of transit damage. In any case, the risk or loss or damage in transit is to be borne by the purchaser. If, upon examination at the factory or Authorized Sonance Dealer, it is determined that

the unit was defective in materials or workmanship at any time during this warranty period, Sonance or the Authorized Sonance Dealer will, at its option, repair or replace this product at no additional charge, except as set forth below. If this model is no longer available and can not be repaired effectively, Sonance, at its sole option, may replace the unit with a current model of equal or greater value. In some cases where a new model is substituted, a modification to the mounting surface may be required. If mounting surface modification is required, Sonance assumes no responsibility or liability for such modification. All replaced parts and product become the property of Sonance. Products replaced or repaired under this warranty will be returned to the original retail purchaser, within a reasonable time, freight prepaid.

This Warranty does not include service or parts to repair damage caused by accident, disaster, misuse, abuse, negligence, inadequate packing or shipping procedures, commercial use, voltage inputs in excess of the rated maximum of the unit, or service, repair or modification of the product which has not been authorized or approved by Sonance. This Warranty also excludes normal cosmetic deterioration caused by environmental conditions. This Warranty will be void if the Serial Number on the product has been removed, tampered-with or defaced. This Warranty is in lieu of all other expressed warranties. If the product is defective in materials or workmanship as warranted above, the purchaser's sole remedy shall be repair or replacement as provided above. In no event will Sonance be liable for any incidental or consequential damages arising out of the use or inability to use the product, even if Sonance or a Authorized Sonance Dealer has been advised of the possibility of such damages, or for any claim by any other party.

Some states do not allow the exclusion or limitation of consequential damages, so the above limitation and exclusion may not apply. All implied warranties on the product are limited to the duration of this expressed Warranty. Some states do not allow limitation on the length of an implied warranty. If the original retail purchaser resides in such a state, this limitation does not apply.

Exclusions and Limitations

The Warranty set forth above is in lieu of all other warranties, express or implied, of merchantability, fitness for a particular purpose, or otherwise. The Warranty is limited to Sonance products registered herein and specifically excludes any damage to loudspeakers and other allied or associated equipment which may result for any reason from use with this product. Sonance shall, in no event, be liable for incidental or consequential damages arising from any breach of this Warranty or otherwise. This Warranty gives you specific legal rights, and you may have other rights which vary from state to state.

©2006 Sonance. All rights reserved. Sonance and OptiLinQ are registered trademarks of Dana Innovations.

Due to continuous product improvement, all specifications are subject to change without notice.
For the latest Sonance product specification information visit our website: www.sonance.com