

ELLIPSE™ 2.0 LCR

FEATURES & SPECIFICATIONS

ELLIPSE 2.0 LCR

The new Sonance Ellipse 2.0 LCR expands our leadership in the In-ceiling Home Theater™ category by raising the bar yet again on In-Ceiling Home Theater speaker performance. Featuring Sonance's proprietary SonicEye™ technology, the Ellipse 2.0 LCR adds a new dampening system for added sonic clarity, higher performance and increased power handling. The baffle of the speaker features a damping pad to absorb reflections generated by the midrange, increasing the sound quality of the speaker. The Ellipse 2.0 LCR features power handling from 5 to 150 Watts and frequency response of 40Hz to 20kHz +/-3dB, providing more bass for larger theater environments.



Key Features:

- In-ceiling Home Theater with Sonance® award winning Sonic Eye™ technology
- Higher performance, more power, more bass for larger theater room environments
- New dampening system for added sonic clarity
- Flexbar® Mounting System
- Compatible with the Ellipse Acoustic Enclosure.

Specifications:

Tweeter: 1.0" (25mm) Pivoting aluminum dome

Midrange: 4.0" (102mm) Pivoting aluminum cone with a rubber surround

Woofer: 6-1/2" (165mm) Black anodized aluminum cone with a rubber surround

Frequency Response: 40Hz - 20kHz ± 3dB

Impedance: 6 ohms nominal - 4 ohms minimum

Power Handling: 5 - 150 Watts

SPL: 90 dB

Grille: Aluminum

Dimensions (W x H x D): 10-1/2" x 15-1/2" x 5-7/8" (267mm x 394mm x 149mm)

Cutout Dims (W x H): 9" x 14" (171mm x 356mm) elliptical

Shipping Weight: 9 lbs (4.1 KG) each

All specifications subject to change without notice



The Leader in Architectural Audio™

WWW.SONANCE.COM

Sonance • 212 Avenida Fabricante • San Clemente, CA 92672-7531 • (800) 582-7777 (949) 492-7777 • FAX (800) 538-5151 (949) 361-5151
©2007 Sonance, all rights reserved. 06/07