



PN.33-1916 3.00

INSTALLATION INSTRUCTIONS

SONANCE SYMPHONY RECTANGLE/ROUND BACK BOX

INTRODUCTION

Thank you for purchasing Sonance Symphony™ speaker accessories. When properly installed, this product will provide you with years of entertainment pleasure. To obtain the full potential of your new speakers and accessories, please read all instructions before starting the installation. If you do not have the necessary skills to install the speakers yourself, contact your Authorized Sonance Dealer for installation options.

PARTS LIST

Each Sonance Symphony_{T/TR} back box package contains:

- (1) Sonance Symphony_{T/TR} back box
- (1) Package wire hole sealant

INSTALLATION INSTRUCTIONS

1. Determine the proper location for the speaker opening.
2. Install the box as far forward (speaker side) in the bay as possible to minimize contact with rear side drywall.
3. Attach the box to the stud or joist bay using wood screws. (Not Included)
4. Drill a quarter inch hole in the top or bottom panel (whichever is more convenient) of the box for the speaker wire.
5. Route the speaker wire into the enclosure through the hole you just drilled and tie a knot to secure it inside.
6. Seal the hole with sealant(included) to make the box air tight.

INSTALLING THE SPEAKERS

1. After the drywall is hung, install the speaker into the back-box opening and secure FlexBar screws on rectangle speakers or RotoLocks on round speakers.
2. Push the grille into place in the speaker frame.

Rectangle back box shown as an example

