# SONANCE

# DSP AMPLIFIER DATA SHEET

# **DSP 2-750 MKIII**

# TECHNICAL SPECIFICATIONS

SKU North America: 93540 | International: 93541

UOM Each

Number of Channels 2 (1 stereo pair)

RMS per Channel @ 8 Ohms 500 watts (2 channels driven)
RMS per Channel @ 4 Ohms 750 watts (2 channels driven)

Peak Bridged @ 8 Ohms 2,000 watts

RMS per Channel @ 70 Volts 750 Watts (2 channels driven)

Frequency Response 5Hz-50kHz, bandwidth limited

Distortion (1kHz) @ 8 Ohms <0.4%, 500W

Distortion (1kHz) @ 4 Ohms <0.3%, 500W

AC Voltage 100-120V@60Hz, 220-240V@50Hz

AC Fuse 15A (T15AL ~ 250V)


Dimensions + Feet (WxHxD) 17.25" x 3.875" x 17.219" (438mm x 98mm x 437mm)

Dimensions + Rack Ears, No Feet (WxHxD) 19" x 3.5" x 17.219" (482mm x 88mm x 437mm)


Rack Space Requirement 2U

Shipping Weight 23.3 lbs. (10.6kg)

# **DIMENSIONAL DRAWINGS**



DSP 2-750 MKIII Amp Back View



DSP 2-750 MKIII Amp Depth View

# **OPTIONAL ACCESSORIES**

### **MODULES AND BRACKETS**

93594
93592
93593
93098

# ASSOCIATED PRODUCTS

#### **DSP AMPLIFIERS**

DSP 2-150 MKIII	93542
DSP 8-130 MKIII	93538

## LIMITED TWO (2) YEAR WARRANTY

Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2023 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.