SONANCE

SOUNDBAR DATA SHEET

ADJUSTABLE WIDTH SOUNDBAR

TECHNICAL SPECIFICATIONS

SB46 M SB46 L SKU 93086 93087

UOM

Tweeter Three 1" (25mm) powder-coated aluminum Three 1" (25mm) powder-coated aluminum dome, Ferrofluid cooled, chambered dome, Ferrofluid cooled, chambered

Midrange Three 4" (102mm) Keylar/Nomex Three 4" (102mm) Keylar/Nomex

laminated cone, rubber surround laminated cone, rubber surround

Woofer Six 4.5" (114mm) Keylar/Nomex Six 4.5" (114mm) Keylar/Nomex laminated cone, rubber surround

laminated cone, rubber surround

Frequency Response 90Hz-20Hz +/-3dB 90Hz-20Hz +/-3dB

Impedance 8 Ohms nominal; 6 Ohms minimum 8 Ohms nominal: 6 Ohms minimum

Power Handling 50 Watts minimum: 150 Watts maximum 50 Watts minimum: 150 Watts maximum

Sensitivity 88dB SPL (2.83V/1 meter) 88dB SPL (2.83V/1 meter)

Grille Material Perforated steel Perforated steel


5.281" x 2.5625" (134mm x 65mm) Dimensions (HxD) 5.281" x 2.5625" (134mm x 65mm)

Adjustable Width (W) 43.875" to 59.625" (1114mm to 1514mm) 61.5" to 77.3125" (1562mm to 1964mm)

Display Diagonal Size Range 50" - 65" (127cm - 165cm) 70" - 80" (178cm - 203cm)

Product Weight 21 lbs (9.5 kg) 26 lbs (11.8 kg) Shipping Weight 30 lbs (13.6 kg) 35 lbs (15.9 kg)

DIMENSIONAL DRAWINGS



ASSOCIATED PRODUCTS

VP46R SST/SUR	93023
VP66R SST/SUR	93025
VPSUB	93352
DSP 8-130 MKII Amplifier	93331
i12 Cabinet Subwoofer	93358
i10 Cabinet Subwoofer	93357
i8 Cabinet Subwoofer	93356

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2021 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.