

SONANCE

BEYOND SOUND

PROFESSIONAL SERIES - PS-S210SUBT Dual 10" Bandpass Subwoofer



Features and Benefits

- Dual 10" drivers
 - Specifically designed and engineered in-house by Sonance for this application
- Low profile design
 - Designed to go under banquets, booths, furniture with supplied feet
 - Mounted on rafters, walls or ceilings with optional C-Bracket
- Port can be moved from front to side, by swapping with blank plate
 - Ensuring optimum sonic performance in any location
- Sonance Laminated Core Technology transformer (SLCT)
 - Full-fidelity performance in 70V/100V
- Built-in low pass filter (crossover)
- The combination of the transformer and bandpass filter, allows the PS-S210SUBT to be driven on the same line as the other full-range speakers in a system
 - Eliminating the need for dedicated amplifier channel with DSP
- Removable grille to keep enclosure free of foreign objects
- Side connector cover with cable management

Specifications

- Frequency response: 44Hz - 132Hz @ -3dB
- Crossover point: 150Hz
- Sensitivity: 94dB
- Maximum SPL (free space): 121dB @ 1m, (127dB peak)
- Tap settings: 300W, 150W, (75W 70V), 4 Ohm
- Dimensions: 9" H x 33" W x 13.78" D (228mmx 838mm x 350mm)
- Net Weight: 61 lbs (27.7 kgs)
- Drivers: Dual 10" woven glass fiber cones Butyl with rubber surrounds
- Input Connector: Four pin, Euroblock with loop output connections
- Cabinet: Polyurethane coated laminated plywood
- Suspension points: 4 x M10 on two sides
- Optional accessory: C-Bracket with 4 x mounting bolts