SONANCE

DATA SHEET

R10SUB | R12SUB REFERENCE SUBWOOFER

TECHNICAL SPECIFICATIONS

R10SUB SKU 93354

UOM

10" (254mm) laminated carbon fiber 12" (305mm) laminated carbon fiber Woofer cone with a rubber surround cone with a rubber surround

Frequency Response 30Hz - 250Hz +/-3dB 25Hz - 250Hz +/-3dB

Impedance 8 Ohms nominal 8 Ohms nominal

Sensitivity 88dB (2.83V/1) meter 90dB (2.83V/1) meter

Grille Material Perforated steel Perforated steel

Required Enclosure R10SUB ENC acoustic enclosure R12SUB ENC acoustic enclosure

(sold separately) (sold separately)

Required Amplification DSP 2-150 or DSP 8-130 MKII DSP 2-750


(two channels bridged) (stereo setting)

10.4375" x 10.4375" x 3.156" 12.375" x 12.375" x 3.156" Dimensions (WxHxD) (265mm x 265mm x 80.2mm) (314mm x 314mm x 80.2mm)

14.25" x 47.25" x 3.4375" 14.25" x 70.875" x 3.4375" Enlcosure Dimensions (WxHxD) (362mm x 1800mm x 87mm)


(362mm x 1200mm x 87mm) (Sold Separately)

DIMENSIONAL DRAWINGS



10.4375" (265mm)

R10Sub **Front View**



12.375" (314mm)

R12SUB **Front View**

ASSOCIATED PRODUCTS

R12SUB

93355

R10SUB ENC /Each 92874 R12SUB ENC /Each 92875 DSP 2-150 MKII /Each 93378 DSP 2-750 MKII /Each 93379

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

2.375"

(314mm)