SONANCE

DATA SHEET

R1C | R1CSUR REFERENCE IN-CEILING SPEAKER

TECHNICAL SPECIFICATIONS

SKU 93351 UOM Each

1" (25mm) Ceramic dome, Ferrofluid-Tweeter cooled in an acoustic back chamber

Midrange 5.25" (133mm) Carbon fiber/Rohacell

laminated cone with a rubber surround

R1C

Woofer Two 5.25" (133mm) Carbon fiber/Rohacell

laminated cones, rubber surrounds

Frequency Response 70Hz - 30Hz +/-3dB

8 Ohms nominal; 6 Ohms minimum Impedance

Power Handling 5 Watts minimum: 150 Watts maximum

Sensitivity 90dB SPL (2.83V/1 meter)

Dimensions 13.78" x 13.78" x 7.5625" (WxHxD) (350mm x 350mm x 192mm)

Cut-Out Dimensions 12.375" x 12.375" (WxH) (314mm x 314mm)

Shipping Weight 15 lbs (7 kg) **R1CSUR**

93352

Two 1" (25mm) Ceramic dome, Ferrofluidcooled in an acoustic back chamber

Two 5.25" (133mm) Carbon fiber/Rohacell laminated cone with a rubber surround

Two 5.25" (133mm) Carbon fiber/Rohacell laminated cones with rubber surrounds

70Hz - 30Hz +/-3dB

8 Ohms nominal; 6 Ohms minimum

5 Watts minimum: 150 Watts maximum


90dB SPL (2.83V/1 meter)

13.78" x 13.78" x 7.5625" (350mm x 350mm x 192mm)

12.375" x 12.375" (314mm x 314mm)

15 lbs (7 kg)


DIMENSIONAL DRAWINGS



13.78" (350mm) **Front View**

7.5625" (192mm)

Side View



Includes back plate compatible with third party seismic retention hardware.

ASSOCIATED PRODUCTS

Flex Bracket /Each 92800

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2021 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.