# SONANCE

# VISUAL PERFORMANCE DATA SHEET

# **VP65 XT | VP65R XT | VP65S XT | VP65R SST XT**

### TECHNICAL SPECIFICATIONS

	<b>VP65 XT</b> 92751	<b>VP65R XT</b> 92752	<b>VP65S XT</b> 92835	<b>VP65R SST XT</b> 92753
SKU	Pair	Pair	Pair	Each
UOM	1" (25mm)	1" (25mm)	1" (25mm)	Two 1" (25mm)
	polyurethane dome	polyurethane dome	polyurethane dome	polyurethane domes
<b>Woofer</b> r	6.5" (165mm) injection-	6.5" (165mm) injection-	6.5" (165mm) injection-	6.5" (165mm) injection-
	molded polypropylene	molded polypropylene	molded polypropylene	molded polypropylene
	graphite cone, integral	graphite cone, integral	graphite cone, integral	graphite cone, integral
	Santoprene surround	Santoprene surround	Santoprene surround	Santoprene surround
Frequency Response	55Hz-20kHz +/-3dB	55Hz-20kHz +/-3dB	55Hz-20kHz +/-3dB	55Hz-20kHz +/-3dB
Impedance	8 Ohms nominal;	8 Ohms nominal;	8 Ohms nominal;	8 Ohms nominal;
	6 Ohms minimum	6 Ohms minimum	6 Ohms minimum	6 Ohms minimum
Power Handling	5 watts minimum;	5 watts minimum;	5 watts minimum;	5 watts minimum;
(RMS)	130 watts maximum	130 watts maximum	130 watts maximum	130 watts maximum
Sensitivity (2.83V/1m)	89dB SPL	89dB SPL	89dB SPL	89dB SPL
Product Dimensions	8.375" x 12.25" x 2.5"	9.75" x 3.5"	9.875" x 9.875 x 3.5"	9.75" x 3.5"
(WxHxD or DiaxD)	(213mm x 311mm x 64mm)	(248mm x 89mm)	(251mm x 251mm x 89mm)	(248mm x 89mm)
Cut-Out Dimensions	6.9375" x 10.75"	8.25"	8.25" x 8.25"	8.25"
(WxH or Dia)	(176mm x 273mm)	(210mm)	(210mm x 210mm)	(210mm)
Shipping Weight	12 lbs. (5.4kg)	12 lbs. (5.4kg)	12 lbs. (5.4kg)	4.5 lbs. (2.1kg)

#### **ASSOCIATED PRODUCTS**

#### **VP65 XT**

Medium Rectangle Retrofit Enclosure / Pair	92342
Medium Rectangle Flex Bracket / 5xPair	92336
Medium Rectangle Masonry Bracket / Pair	92066
Medium Rectangle Acoustic Enclosure / Each	91687
Fire-Rated Listed Shallow Backcan / Each	92807

#### VP65R XT & VP65R SST XT

Medium Round Flex Bracket / 5xPair	92337
Medium Round Retrofit Enclosure / 5xPair	92343
Medium Round Acoustic Enclosure / Pair	91688
Fire-Rated Listed Deep Backcan / Each	92808

#### VP65S XT


Medium Square Acoustic Enclosure / Each	92474
Medium Round/Square Retrofit Enclosure / 5xPair	92343
Medium Square Flex Bracket / 5xPair	92344
Fire-Rated Listed Deep Backcan / Each	92808

**LIMITED FIVE (5) YEAR WARRANTY** Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2020 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.


SONANCE • 991 Calle Amanecer • San Clemente, CA 92673 USA • Phone: (949) 492-7777 • Fax: (949) 361-5151 • Technical Support: (949) 492-7777 • www.sonance.com 12.30.2020

## **DIMENSIONAL DRAWINGS**




8.375" (213mm)

VP65 XT **Front View** 




2.5" (64mm)

VP65 XT **Side View** 




9.75" (248mm)


#### **VP65R XT Front View**




**VP65R XT Side View** 



**VP65S XT Front View** 




**VP65S XT Side View** 



9.75" (248mm)

#### **VP65R SST XT Front View**



**VP65R SST XT Side View**