VISUAL PERFORMANCE® SERIES

SONANCE°

VP62R, VP64R, VP66R, VP68R, + Square Adapter

Product Family Overview

From the company that invented the category, comes the **BEST SOUNDING**, best looking and most complete range of in-wall and in-ceiling speakers ever. Visual Performance® Series

comes in various shapes and sizes to compliment down lights and décor and a complete range that allows you to enjoy a consistent aesthetic for any application in any room.



Features and Benefits

Absolute best sonic performance at all price points

 Designed using state-of-the-art computer modeling software to vastly improve magnetic field and suspension linearity for consistent sonic performance at any SPL for best-in-class performance

Latest high-tech driver and tweeter material technology

- Improved low frequency performance
- Improved driver cone materials
- Low diffraction woofer and tweeter design
- Pivoting woofer and tweeter for improved frequency response in off-axis installations
- Chambered tweeter design on all models

The chambered tweeter design does the following

- Lowers the resonance frequency of the tweeter
- Allows for a lower crossover frequency to the woofer
- Reduces the back pressure on the tweeter dome
- Reduces the distortion of the tweeter near the crossover frequency

Easier to install

- Easier to access Roto-Lock® screws
- Removed metal hang tabs
- One-piece paintable grille with peel and stick scrim cloth for easier painting
- Two piece toggle feet allows installation with double dry wall and thicker ceiling and wall materials

Square adapter w/ grille can turn any round speaker into a square speaker


- Allows easy alignment of the square grille with other ceiling features
- Available in 1 pair or 5 pair bulk packages


Specifications


Diameter: 9 3/4" (248mm)
Depth: 4 3/4" (121mm)
Cut Out Diameter: 8 1/4" (210mm)

With Square Adapter and Grille

Width: 9 7/8" (210mm) Height: 9 7/8" (210mm)





















SPECIFICATIONS

VP62R +VP6SQ

VP64R + VP6SC

VP66R +VP6SG

SKU	93012	93013	93014	93015	
UOM	Pair	Pair	Pair	Pair	
Tweeter	1" (25mm) cloth dome,	1" (25mm) powder coated	1" (25mm) powder coated	1" (25mm) ceramic dome,	
	Ferrofluid-cooled, pivoting,	aluminum dome, Ferrofluid-cooled,	aluminum dome, Ferrofluid-cooled,	Ferrofluid-cooled, pivoting,	
	in acoustic back chamber	pivoting, in acoustic back chamber	pivoting, in acoustic back chamber	in acoustic back chamber	
Woofer	6 1/2" (165mm) textured polypropylene cone with a rubber surround, pivoting	6 1/2" (165mm) textured polypropylene cone with a rubber surround, pivoting	6 1/2" (165mm) Kevlar / Nomex laminated cone with a rubber surround, pivoting	6 1/2" (165mm) carbon fiber/ Rohacell [®] laminated cone with a rubber surround, pivoting	
Frequency Response	45Hz - 20kHz ± 3dB	45Hz — 20kHz ±3dB	43Hz − 20kHz ±3dB	40Hz − 20kHz ±3dB	
Impedance	8 ohms nominal;	8 ohms nominal;	8 ohms nominal;	6 ohms nominal;	
	6 ohms minimum	6 ohms minimum	6 ohms minimum	4 ohms minimum	
Power Handling	5 watts minimum;	5 watts minimum;	5 watts minimum;	5 watts minimum;	
	125 watts maximum	125 watts maximum	140 watts maximum	150 watts maximum	
Sensitivity	89dB SPL	89dB SPL	90dB SPL	90dB SPL	
	(2.83V/1 meter)	(2.83V/1 meter)	(2.83V/1 meter)	(2.83V/1 meter)	
Grille	Perforated steel	Perforated steel	Perforated steel	Perforated steel	
Adjustments	-	-	-	Tweeter Level Switch $$ -3dB Flat $+$ 3dB	
Dimensions	9 3/4" x 4 3/4"	9 3/4" x 4 3/4"	9 3/4" x 4 3/4"	9 3/4" x 4 3/4"	
(Dia. x D)	(248mm x 121mm)	(248mm x 121mm)	(248mm x 121mm)	(248mm x 121mm)	
Dimensions with	9 7/8" x 9 7/8"	9 7/8" x 9 7/8"	9 7/8" x 9 7/8"	9 7/8" x 9 7/8"	
Square Grille (W x H)	(251mm x 251mm)	(251mm x 251mm)	(251mm x 251mm)	(251mm x 251mm)	
Cut-Out Dimensions	8 1/4"	8 1/4"	8 1/4"		
(Dia.)	(210mm)	(210mm)	(210mm)		
Shipping Weight	9 lbs (4.1kg) pair	10 lbs (4.5kg) pair	10 lbs (4.5kg) pair	12 lbs (5.5kg) pair	

Associated Products

VP6SQ Square Adapter w/ grille (Pair Per Box)	93030	Medium Round Flex Bracket (5 Pair Per Box)	92337	
VP6SQ Square Adapter w/ grille (5 Pair Per Box)	93033	Fire-Rated Listed Deep Backcan (Each)	92808	
Medium Round Retrofit Enclosure (Pair Per Box)	92343	Medium Round Coverplate (Pair Per Box)	92335	0
Medium Round Acoustic Enclosure (Each)	91688			

LIMITED LIFETIME WARRANTY

Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the life of the Product, except for the grille, which is warranted for five (5) years. Sonance will at its option and expense either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. Please visit our website and owner's e-Manual for complete warranty and exclusion information.



©2013 Sonance. All rights reserved.

Sonance, Visual Performance and Roto-Lock, are registered trademarks of Dana Innovations.

Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website: www.sonance.com

SONANCE • 212 Avenida Fabricante • San Clemente, CA 92672-7531 USA

(800) 582-7777 or (949) 492-7777 • FAX: (949) 361-5151 • Technical Support: (800) 582-0772 www.sonance.com